

MICRO POWDER TECH

Company Profile

MICRO POWDER TECH is a firm established in the year 1997 by **S.C.Jain** having experience since 1980 in production of Paints & Coatings.

Our range of machinery is essentially small scale and low cost compared with all other major suppliers & a unique package for the manufactures entering Powder Coating Production.

A range of machinery designed by ourselves **Twin Screw Extruder MPT-30PC, MPT-45,MPT-60 & MPT-65 and Air Classifying Mill (Grinding Mill)** with low power consumption to produce quality Powder Coating Paints & incorporating design features for easy clean down & maintenance with a Technical Knowhow. This together with a technology package tailored to suit the requirements of the small medium size entrants into the Powder Coating Industry.

We have laboratory with most modern equipment for R & D. New formulation and testing facilities are provided to customers. Whether its small scale rapid response production or large scale bulk powder manufacturer. MICRO POWDER TECH has experience to supply an efficient system to match customers requirements. We can offer you the right equipment, which is up to date, reasonable, simple and at extremely competitive price.

We export to **Japan, Bangla Desh, Russia, Ukraine ,Iran, Africa, Europe & USA** which are in production with successful quality compatible.

With guaranteed performance to match the international Standard quality of Powder Coating Production Package :

# A Big Production Package	(400 – 500 Kg./Hr.)
# A Large Production Powder Coating Plant	(300 – 340 Kg./Hr.)
# A Medium Production Powder Coating Plant	(140 – 180 Kg./Hr.)
# A Lab-Small Production Powder Coating Plant	(Min. 0.400 Kg. Max. 20 – 30 Kg./Hr.)
# A Lab Model Powder Coating Machine	(Min. 0.250 Kg. Max. 6 - 8 Kg./Hr.)

Each Powder Coating Plant comprises: * Premixer * Twin Screw Extruder * Chill Roll Belt

* ACM MPT- Grinding Mill * Sieving Machine with Technical Know how.

In **INDIA** more then 65% Powder Coating Production Plants are in chain of our installations & are running successfully.

We are very much Sincere, Honest, Hardworking and Innovating to solve problems of our clients. We maintain delivery schedule. We give guarantee for the performance of our products.

We are manufacturing product, what small- scale industry cannot manufacture and big manufacturer cannot provide. We manufacture only tailor made and difficult products with performance guarantee.

MICRO POWDER TECH

Plot No.48, Sector-24,
Faridabad – 121005
Haryana, India.
Ph. : 91-129-4023335,
Mobil :+919811116490, +919810460909
E-mail: info@micropowdertech.in
Website : www.micropowdertech.in

Powder Coating Production 300 - 340 Kg. / Hr. Plant

1. Pre Mixer SS-100
2. Twin Screw Extruder MPT 60 PC with Chill Roll & Flaker
3. ACM Grinding Mill MPT-20
4. Sifter-36 (Sieving Machine)



PREMIXER SS-100

TWIN SCREW EXTRUDER MPT 60PC WITH CHILL ROLL & FLAKER



ACM GRINDING MILL MPT-20



SIEVING MACHINE

MICRO POWDER TECH

Powder Coating Production 300 - 340 Kg. / Hr. Package

TECHNICAL DATA

<u>Premixer High Speed Batch Mixer</u>		
Model		SS-100
Main Drive		7.5 KW
Cooling Arrangement		N/A
Vessel material		Stainless Steel
Vessel Volume		200 Ltrs. Aprox.
Batch Capacity		80-100 Kg. Cycle
<u>Twin Screw Extruder</u>		
Product/Model		Twin Screw Extruder MPT-60 PC
Capacity	Kg / h	300-340
Extruder	Type	Twin Screw
Model		MPT-60PC
L / D		18 : 1
Screw Dia.	mm	60
Screw speed	Rpm	0-450
Main power	Kw	22.5 KW
Drive type		AC frequency drive
Make		Schneider Electric
Heating power	Kw	6 KW
Vol. feeder with hopper		
Hopper volume	Liter	72 Liters
Power with AC frequency drive	Kw	0.75 Kw
Capacity	Kg / h	20 to 500 kg / h
No of heating/cooling zones		3 zone
Heating Type		Cartridge heaters
Screw shaft		Hexagonal section hard chrome
Screw elements		Feed screw, paddles intermeshing
Barrel		Split type opening, Segmented liner insert.
Vol screw feeder		Speed variable screw feeder
Gear box		High efficiency, forced lubrication with cooling arrangement
Control voltage	V	220 Volt
CHW flow rate	Lph	1700 liter / h
Temperature	°C	10 to 12 °C

Cont. Page-2 Production 300-340 Kg. Package

Controls & Instrumentation		
PID Control		PID Controlled 2 Nos.
Speed		AC frequency drive
Temperature		PID Digital temp.
Display provided in panel		
	Motor speed	Digital Screw RPM Meter
	Output voltage	415 Volt
	Frequency	50 Hz
	Current	AMP Digital Meter
	Power	3Phase indicator, Volt Meter
	Drive temp.	Frequency drive internal feature
	Hour counter	Digital / Analogue
Protections (Electrical and Machine interlocks)		
	Drive temp.	Drive internal protection
	Motor load	Drive internal protection
	Under voltage	SPP
	Earth fault	SPP
	Mains supervision	MCB
	Phase supervision	Digital volt meter, Phase indicator
Chill Roll & Flaker		
Model		CR TS - 55
MOC		S.S. Chill Roller
Main drive with AC frequency drive	Kw	2.25 KW
Flaker power	Kw	0.75 KW
CHW flow rate	Lpm	260 liter / min.
---do-- temperature	°C	10 to 12° C
Space requirement	L x W x H, in mm	
Extruder	MM	L-1950 X W-870 X H-2700
Flaking system	MM	L-2000 X W-1450 X H-1300
Assembly weight	Kgs or tons	
Extruder	Kgs	App. 1800 Kg.
Flaking system		.

Continue P-3 Production 300-340 Kg./Hr. Package


ACM-20 Grinding Mill		
Model		ACM MPT-20
Mill Motor		11.25 KW
Blower Motor		15 KW
Classifier Motor with AC frequency drive		1.5 KW
Feeder Motor with AC frequency drive		0.75 KW
Plus Jet Valve		6 Nos. Solenoid Valve
Cyclone		Stainless Steel
Dust Collector		22 Sq. Mtrs Filter Area
Feeder Unit		Screw feeding S.S. Constructed
Classifier RPM		700 - 3000
Air Flow		1400 CFM
Overall Dimensions Mtrs.		L-6 X W-2.0 X H- 3.5
Butterfly Valve assembly	Power supply	230 volt
Production Capacity		240 - 280 Kg. / Hr.
Sieving Machine (Sifter)		900 mm
Electric Motor		1.125 KW
Capacity		240-280 Kg./Hr.

Free Spare Parts :-

1. One Pair of Screw Set.
3. Cartage Heater One set (10 Nos.)
4. Hammer set one.

NOTE : Product specifications are subject to change without prior notice.

MANUFACTURE OF POWDER



PREMIXING

At first the ingredients are weighed & premixed in an absolute dry condition.

EXTRUSION

The premixed materials are then continuously charged in the extruder. Here the binder melts and dispersed with all other ingredients.

COOLING & FLAKING

The extruder material is chilled very fast & flattened as sheet by chilled rollers on conveyor belts. The chilled product is crushed into flakes.


MILLING & SIEVING

The flakes are then milled and sieved up to required particle sizes.

PACKING

The sieved powder is then packed in Poly bag & corrugated box.

PLAN & LAYOUT FOR MACHNES



EXCLUSIONS OUR PACKAGE

THE ITEMS LISTED BELOW ARE REQUIRED

1. WATER CHILLER 10 TON
2. AIR CHILLER 5 TON
3. POLYTHEN SEALING MACHINE 20"
4. ELECTRONIC BALANCE 1 KG.(Lees count 0.1 Grams)
5. WEIGHT BALANCE UP TO 10 KG.
WITH WEIGHT UP TO 10 KG.
6. S. S Tank for Chips collection (2 Nos.) Size L-900mm X W- 600mm X H-500mm
6. PLASTIC CARRET 25 NOS.
SIZE- 600X400X300 MM.
7. PLASTIC BARREL 200 LTRS 5 NOS.
8. PVC PIPE $\frac{3}{4}$ " – 20 MTRS
9. JHABBA 4 NOS.
10. FILTER CLOTH 140 MESH- 20 MTRS
160 MESH- 20 MTRS
400 MESH- 5 MTRS.
11. ELECTRICAL WIRING & FITTINGS.
12. HOSE PIPE 4" -- 3 Mtrs. For Air Chiller.

LABORATORY TESTING INSTRUMENTS

1. GLOSS METER 60 HEAD.
2. **TUBLER IMPACT TESTER 250 KG, CM.**
3. **ELECTRICCAL OVEN 250 C**
AIR CERCULATING. 14"X14"
4. TEST SIEVE 25 MICRON 4".
5. GEL TIME APPRATUS
6. BALANCE 1 MG.
7. MELTING POINT APPARATUS
8. **POWDER COATING SPREY GUN & BOOTH (LAB MODEL)**
9. **KITCHEN MIXY**
10. **COMPRESSER 2 HP.**

Note : Laboratory Testing Instruments are No. 2, 3, 8, 9 & 10 are must.